

TECHNICAL SPECIFICATIONS

9200 Air Drill	9,1 mts	11 mts	14 mts	18,4 mts
Number of openers	48	58	72	96
Row spacing	19,1 cm	19,1 cm	19,1 cm	19,1 cm
Chassis type				
	Flexible with 3 sections with floating hitch, hydraulically folding wings for transporting			Flexible with 5 sections with floating hitch. Hydraulically folding wings for transporting
Single-disc opener				
Disc diameter	18"			
Disc angle	7°			
Gauge wheels	Standard: 4,5"x16" Semi-pneumatic. Optional: 4,5"x16" Semi-pneumatic ribbed.			
Press wheels	Semi-pneumatic 1x10"			
Closing wheels	Standard: 1"x12" nodular cast and 20° vertical. Optional: 14" star discs.			
Openers hydraulics	Active hydraulic downpressure of up to 204 kg per opener.			
General dimensions				
Distance between trees	1500 mm			
Ground clearance	22 cm			
Working width	9,1 mts	11 mts	14 mts	18,4 mts
Transport width	4,4 mts	4,4 mts	5,4 mts	6 mts
Transport gauge	2,5 mts	2,5 mts	3,3 mts	3,8 mts
Transport height	3,6 mts	4,5 mts	5,6 mts	4,9 mts
Weight	8200 Kg.	9700 Kg.	13.500 Kg.	20.500 Kg.
Tyres	12 tyres 11 L 15.10 PR			18 tyres 400/6015,5
Required power	170 HP	200 HP	250 HP	330 HP